



“Quality, experience and responsiveness are guaranteed when you do business with SpaceAge Synthetics, Ltd.”

SpaceAge Synthetics offers a product line with several densities, compositions and thicknesses to suit endless applications that require a water resistant, lightweight, high strength material. We welcome you to contact one of our knowledgeable Sales Reps today to determine which product is right for you.

Our Thermo-Lite Board® is manufactured with the finest polyurethane and fiberglass available, and is offered in thicknesses from .25” to 2”, dimensions up to 60” wide and 170” long, and a density range of 10-45 lbs per cubic foot.



Thermo-Lite Board® Core

Made with a filter fiberglass lay-up, this product is a good coring material in niche applications.

Thermo-Lite Board® Versatile

Made with a matt fiberglass lay-up, this product is a great choice for a wide variety of uses from floor to ceiling.

Thermo-Lite Board® Tough

Made with a medium-weight woven fiberglass lay-up, this product is acceptable for standard structural loading applications.

Thermo-Lite Board® Supreme

Made with a ultra-heavy weight woven fiberglass lay-up that offers superior mechanical properties, making it the ultimate product where the utmost specific structural strength is required.

	Sample Applications of Thermo-Lite Board®			
	Core	Versatile	Tough	Supreme
Cores for glass layup applications	X	X		
Cabinetry & Shelving		X		
Transportation bulkheads and ceilings		X		
Marine bulkheads, stringers		X		
Marine transoms, hatches and seats		X		
Props, signs and theme park structures		X		
Wash-down areas		X	X	X
Equipment sheds and enclosures		X	X	X
Communication towers		X	X	X
Staging and concert flooring		X	X	X
Marine flooring			X	X
Lab and Cooler walls and flooring			X	X
Transportation flooring			X	X

Please Contact Us:



SpaceAge Synthetics, Ltd.
1402 39th Street NW
Fargo, ND 58102 USA
Tel: 701.277.5631
Fax: 701.277.5689

www.spaceagesynthetics.com