

PRODUCT AVAILABILITY MATRIX

Thermo-Lite Board®

| THERMO-LITE BOARD® (Series: 3 rd Position) | SHEET THICKNESS | DENSITY RANGE (Series: 1 st & 2 nd Position) | | | SHEET SIZE Up to Largest Width X Length |
|---|---------------------------|---|--|-----------------------------|--|
| | | Lightest lb/ft ³ (sanded 2 sides) | Lightest lb/ft ³ (sanded 1 side or non sanded) | Heaviest lb/ft ³ | |
| VERSATILE CFM fiberglass reinforced (0) | .25 in 6 mm | 26 | 30 | 40 | 5 x 16 ft 1525 X 4880 mm |
| | .375 in 9 mm | 24 | 24 | 38 | 5 x 16 ft 1525 X 4880 mm |
| | .5 in 12 mm | 20 * | 24 | 34 | 5 x 16 ft 1525 X 4880 mm |
| | .75 in 19 mm | 18 * | 22 | 34 | 5 x 16 ft 1525 X 4880 mm |
| | 1 in 25 mm | 18 * | 22 | 34 | 5 x 16 ft 1525 X 4880 mm |
| | 1.25 - 2 in 31 - 50 mm | 18 * | 22 | 32 | 4 x 8 ft 1220 X 2440 mm |
| CORE Filter lay-up (3) | .25 in 6 mm | 20 * | 24 | 30 | 5 x 10 ft 1525 X 3050 mm |
| | .375 in 9 mm | 17 * | 22 | 30 | 5 x 10 ft 1525 X 3050 mm |
| | .5 in 12 mm | 14 * | 18 | 30 | 5 x 10 ft 1525 X 3050 mm |
| | .75 in 19 mm | 10 * | 14 | 30 | 5 x 10 ft 1525 X 3050 mm |
| | 1 in 25 mm | 10 * | 14 | 30 | 5 x 10 ft 1525 X 3050 mm |
| | 1.25 - 2 in 31 - 50 mm | 10 * | 14 | 25 | 4 x 8 ft 1220 X 2440 mm |
| TOUGH CFM & 18 oz. woven fiberglass reinforced (5) | .25 in 6 mm | 38 | 40 | 44 | 5 x 10 ft 1525 X 3050 mm |
| | .375 in 9 mm | 34 | 36 | 40 | 5 x 10 ft 1525 X 3050 mm |
| | .5 in 12 mm | 28 | 28 | 36 | 5 x 10 ft 1525 X 3050 mm |
| | .75 in 19 mm | 26 | 28 | 34 | 5 x 10 ft 1525 X 3050 mm |
| | 1 in 25 mm | 26 | 28 | 32 | 4 x 10 ft 1220 X 3050 mm |
| | 1.50 in 38 mm | 24 | 26 | 30 | 4 x 10 ft 1220 X 3050 mm |
| SUPREME CFM & 24 oz. woven fiberglass reinforced (6) | .25 in 6 mm | 40 | 42 | 46 | 5 x 10 ft 1525 X 3050 mm |
| | .375 in 9 mm | 34 | 38 | 42 | 5 x 10 ft 1525 X 3050 mm |
| | .5 in 12 mm | 28 | 28 | 38 | 5 x 10 ft 1525 X 3050 mm |
| | .75 in 19 mm | 26 | 28 | 34 | 5 x 10 ft 1525 X 3050 mm |
| | 1 in 25 mm | 26 | 28 | 32 | 4 x 10 ft 1220 X 3050 mm |
| | 1.50 in 38 mm | 24 | 26 | 30 | 4 x 10 ft 1220 X 3050 mm |

1 lb/ft³ = 16.018 kg/m³

*The lowest density product can only be 4 ft wide

** Other dimensions and densities beyond this matrix are possible but must be approved

SURFACE OPTIONS

(Series: 4th Position)

| | <u>Side A</u> | <u>Side B</u> |
|-----|---------------|---------------|
| (0) | Elephant Skin | Elephant Skin |
| (1) | Elephant Skin | Sanded |
| (2) | Sanded | Sanded |
| (3) | Natural Skin | Natural Skin |
| (4) | Natural Skin | Sanded |
| (5) | Elephant Skin | Natural Skin |
| (6) | FASCOAT | Sanded |
| (7) | FASCOAT | Elephant Skin |
| (8) | FASCOAT | Natural Skin |
| (9) | FASCOAT | FASCOAT |

EXAMPLE:

Thermo-Lite Board® Series 26 5 2

